

## SELECTION & SPECIFICATION DATA

<b>Type</b>	Modified Asphalt
<b>Description</b>	Blackhawk 5350 Roofing Adhesive is a single-component, asbestos-free asphaltic commercial roofing adhesive designed to adhere modified bituminous membranes, particularly in lower temperatures. It can be sprayed or applied using a squeegee. Blackhawk 5350 Roofing Adhesive demonstrates superior resilience to wind uplift testing with the help of an aggressive solvent. 5350 is comprised of a special, low-odor formula that leads the bituminous roofing industry in adhesion under low-temperature conditions.
<b>Features</b>	<ul style="list-style-type: none"><li>• Aggressive bond in low temperatures</li><li>• Low odor</li><li>• Single-component</li><li>• Cold-applied</li><li>• Flexible</li><li>• Quick-drying</li></ul>
<b>Uses</b>	Adhesive for single- and multi-ply SBS bituminous roofing membranes in lower temperatures.
<b>Color</b>	Black
<b>Primer</b>	Self-priming
<b>Solids Content</b>	77% by weight
<b>Theoretical Coverage Rate</b>	1.5 – 2 gallons per square, depending on substrate
<b>VOC Value(s)</b>	<250 g/L (2.09 lbs/gal)

## SUBSTRATES & SURFACE PREPARATION

<b>All</b>	All surfaces must be clean and free from debris and loose scale material or anything that may interfere with adhesion or act as a bond breaker with the desired substrate.
------------	--

## MIXING AND THINNING

<b>Mixing</b>	Light mixing may be necessary. Ready to use if sealed properly in ideal storage conditions.
<b>Thinning</b>	Not recommended

## APPLICATION EQUIPMENT GUIDELINES

<b>Airless Spray</b>	Pump Size - 45:1 or greater Spray Hose - 200 ft maximum x 3/4 in ID Whip - 15 ft x 1/2 in ID
<b>Squeegee</b>	1/4 in serrated squeegee

## CLEANUP & SAFETY

<b>Cleanup</b>	Mineral spirits or similar solvent
<b>Safety</b>	Mixes and applications of this product present a number of hazards. Read and follow the hazard information, precautions and first aid directions on the individual product labels and safety data sheets before using.
<b>Ventilation</b>	Use in well ventilated areas

## PACKAGING, HANDLING & STORAGE

<b>Shelf Life</b>	12 months at 75°F (24°C) When kept at recommended storage conditions and in original unopened containers.
<b>Package Sizes &amp; Shipping Weights</b>	5 gallon pail - 45 lbs (20.4 kg) 55 gallon drum - 490 lbs (222 kg) 275 gallon tote - 2450 lbs (125 kg) 350 gallon returnable tote - 3400 lbs (159 kg)
<b>Storage Temperature &amp; Humidity</b>	40°F – 110°F (4°C – 43°C) 0 – 100% relative humidity
<b>Storage</b>	Storage indoors is recommended. Always inspect the product prior to use.

## PERFORMANCE DATA

Lap shear testing after 24 hours has shown that Blackhawk 5350 meets or exceeds the performance attributes of ASTM D3019.

Rev 07/19

### TERMS AND CONDITIONS OF SALE

While statements, technical information and recommendations contained herein are based on information our company believes to be reliable, nothing contained herein shall constitute any warranty, express or implied, with respect to the products and/or services described herein and any such warranties are expressly disclaimed. We recommend that the prospective purchaser or user independently determine the suitability of our product(s) for their intended use. No statement, information or recommendation with respect to our products, whether contained herein or otherwise communicated, shall be legally binding upon us unless expressly set forth in a written agreement between us and the purchaser/user. For all Terms and Conditions of Sale see [ergonarmor.com](http://ergonarmor.com).