SAFETY DATA SHEET



1. Identification

Product identifier PENNTROWEL™ VINYL ESTER PRIMER RESIN

Other means of identification None.

Recommended use For industrial use only.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

ErgonArmor, a division of Ergon Asphalt & Emulsions, Inc. **Company Name**

Address 2829 Lakeland Drive Jackson, MS 39232

USA

After hours telephone

number

Normal work hours

telephone number

1-877-982-7667

1-800-222-7122

Website www.ergonarmor.com E-mail sds@ergon.com

Emergency 24-hour telephone number

CHEMTREC: North America 1-800-424-9300 International 1-800-527-3887

Information on operation

hours

8:00 a.m. to 5:00 p.m.

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 **Health hazards** Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Germ cell mutagenicity Category 1 Carcinogenicity Category 1

Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified. **OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. May cause an allergic skin reaction. May cause genetic defects. May cause cancer.

Causes damage to organs through prolonged or repeated exposure.

Precautionary statement Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Contaminated work clothing should not be allowed out of the workplace.

Response IF ON SKIN: Wash with plenty of water. IF ON SKIN (or hair): Remove/Take off immediately all

contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Specific treatment see Section 4 of this SDS. Take off contaminated clothing and wash before reuse. In case of fire: Use appropriate media to

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

extinguish.

Supplemental information Not applicable.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
STYRENE		100-42-5	20 - 50
AROMATIC 100 - 7.29		64742-95-6	0.200 - 0.220
COBALT(II) 2-ETHYLHEXANG	DATE	136-52-7	0.080 - 0.140

4. First-aid measures

Inhalation Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if

victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Get medical attention

immediately.

Skin contactWash the skin immediately with soap and water. Take off immediately all contaminated clothing.

Wash clothing separately before reuse. Get medical attention if irritation develops and persists.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content

doesn't get into the lungs. Never give anything by mouth to a victim who is unconscious or is

having convulsions. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Irritating to mouth, throat, and stomach. May cause redness and pain. Mild skin irritation. Causes eye irritation. Harmful if inhaled. Dermatitis. Rash. May cause respiratory tract irritation, headache, dizziness, fatigue, confusion, visual disturbance, drowsiness, and weakness. May cause an allergic skin reaction.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. In case of shortness of breath, give oxygen. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Self-contained breathing apparatus and full protective clothing must be worn in case of fire. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch or walk through spilled material. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area).

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Prevent entry into waterways, sewer, basements or confined areas.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with eyes, skin, and clothing. When using do not smoke. When using do not eat or drink. Avoid breathing dust/fume/gas/mist/vapors/spray. Take precautionary measures against static discharges. Flammable vapors may accumulate in the container. Use non-sparking tools. Ground/bond container and receiving equipment. Keep away from sources of ignition - No smoking. Avoid prolonged exposure. Observe good industrial hygiene practices. Provide adequate ventilation. Wash thoroughly after handling.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep containers tightly closed. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in cool place. Keep container in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-2 Permi	ssible Exposure Limits (PEL) (29 CF	R 1910.1000)
Commonto	T	Value

Components	Туре	Value	
STYRENE (CAS 100-42-5)	Ceiling	200 ppm	
	TWA	100 ppm	
US. ACGIH Threshold Limit Valu	es (TLV)		
Components	Туре	Value	Form
COBALT(II) 2-ETHYLHEXANOATE (CAS 136-52-7)	TWA	0.02 mg/m3	Inhalable fraction.
STYRENE (CAS 100-42-5)	STEL	20 ppm	
	TWA	10 ppm	
NIOSH. Immediately Dangerous	s to Life or Health (IDLH) Va	lues, as amended	
Components	Туре	Value	
STYRENE (CAS 100-42-5)	IDLH	0.9 %	
		700 ppm	
US. NIOSH: Pocket Guide to Che	emical Hazards Recommende	ed Exposure Limits (REL)	
Components	Туре	Value	
STYRENE (CAS 100-42-5)	STEL	425 mg/m3	
		100 ppm	
	TWA	215 mg/m3	
		50 ppm	

Material name: PENNTROWEL™ VINYL ESTER PRIMER RESIN 5260 Version #: 01 Issue date: 10-11-2024

Biological limit values

ACGIH Biological Exposi Components	ıre Indices (BEI) Value	Determinant	Specimen	Sampling Time
COBALT(II) 2-ETHYLHEXANOATE (CAS 136-52-7)	15 μg/l	Cobalt	Urine	*
STYRENE (CAS 100-42-5)	20 μg/l	Styrene	Urine	*
	150 mg/g	Mandelic acid plus phenylglyoxylic acid	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

STYRENE (CAS 100-42-5) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

STYRENE (CAS 100-42-5) Skin designation applies.

Appropriate engineering controls

Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style

gloves.

Wear appropriate chemical resistant clothing. Other

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment

to remove contaminants.

9. Physical and chemical properties

Liquid. **Appearance Physical state** Liquid. **Form** Liquid. Color Clear.

Odor Not available. Not available. **Odor threshold** pН Not available. Melting point/freezing point Not available. Initial boiling point and Not available.

boiling range

Flash point 84.9 °F (29.4 °C) **Evaporation rate** Not available. Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Explosive limit - lower (%)

Not available.

Explosive limit - upper

Not available.

(%)

Vapor pressure Not available. Vapor density Not available. Not available. Relative density

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.
(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 8.75 lb/gal

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid

temperatures exceeding the flash point.

Incompatible materials None known.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

InhalationHarmful if inhaled.Skin contactCauses skin irritation.

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms related to the physical, chemical and toxicological characteristics

Exposure may cause temporary irritation, redness, or discomfort. Irritating to eyes, respiratory

system and skin. Mild skin irritation. Irritating to mouth, throat, and stomach.

Information on toxicological effects

Acute toxicity Harmful if inhaled.

Components Species Test Results

COBALT(II) 2-ETHYLHEXANOATE (CAS 136-52-7)

Acute

Oral

LD50 Rat 150 mg/kg

STYRENE (CAS 100-42-5)

<u>Acute</u>

Oral

LD50 Rat 1 g/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritationCauses skin irritation. **Serious eye damage/eye**Irritating to eyes.

irritation

Respiratory or skin sensitization

ACGIH sensitization

Cobalt and inorganic compounds, inhalable fraction, as
Dermal sensitization

Co (CAS 136-52-7)

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity May cause genetic defects.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

AROMATIC 100 - 7.29 (CAS 64742-95-6) 3 Not classifiable as to carcinogenicity to humans.

STYRENE (CAS 100-42-5) 2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

COBALT(II) 2-ETHYLHEXANOATE (CAS 136-52-7)

STYRENE (CAS 100-42-5)

Reasonably Anticipated to be a Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity Not classified. Specific target organ toxicity

- single exposure

Not available.

Specific target organ toxicity

Causes damage to organs through prolonged or repeated exposure.

- repeated exposure Aspiration hazard

Not available.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product Species Test Results

PENNTROWEL™ VINYL ESTER PRIMER RESIN

Aquatic

LC50 Fish Fish 76.195 mg/l, 96 hours

Acute

Crustacea EC50 Daphnia 9.4286 mg/l, 48 hours estimated Fish LC50 Fish 9.4 mg/l, 96 hours estimated

Components Species Test Results

STYRENE (CAS 100-42-5)

Aquatic

EC50 Crustacea Water flea (Daphnia) 42 g/ml, 24 hours

Acute

EC50 Crustacea Water flea (Daphnia magna) 3.3 - 7.4 mg/l, 48 hours Fish LC50 Fathead minnow (Pimephales promelas) 3.29 - 5.05 mg/l, 96 hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

STYRENE 2.95

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Dispose of in accordance with local regulations. Empty containers or liners may retain some Waste from residues / unused products

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Empty containers should be taken to an approved waste handling site for recycling or disposal. Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

Material name: PENNTROWEL™ VINYL ESTER PRIMER RESIN 5260 Version #: 01 Issue date: 10-11-2024

^{*} Estimates for product may be based on additional component data not shown.

14. Transport information

DOT

UN number UN1866

UN proper shipping name Resin solution, flammable

Transport hazard class(es)

Class 3 **Subsidiary hazard** Label(s) 3 **Packing group** TTT **Environmental hazards**

> Marine pollutant NO

Special precautions for Not assigned.

Special provisions B1, B52, IB3, T2, TP1

Packaging exceptions 150 Packaging non bulk 173 Packaging bulk 242

IATA

UN1866 **UN** number

UN proper shipping name Resin solution flammable

Transport hazard class(es)

Class 3 **Subsidiary hazard Packing group** III **Environmental hazards** No. **ERG Code** 3L Not assigned.

Special precautions for

user

Other information

Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

Allowed with restrictions.

IMDG

UN number UN1866

UN proper shipping name **RESIN SOLUTION flammable**

Not available.

Transport hazard class(es)

3 Class **Subsidiary hazard Packing group** III

Environmental hazards

Marine pollutant No. **EmS** F-E, S-E Not assigned. **Special precautions for**

Transport in bulk according to

Annex II of MARPOL 73/78

and the IBC Code

DOT





15. Regulatory information

US federal regulations

All components are on the U.S. EPA TSCA Inventory List.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

COBALT(II) 2-ETHYLHEXANOATE (CAS 136-52-7) Listed. STYRENE (CAS 100-42-5) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

categories

SARA 311/312 Hazardous Yes

chemical

Classified hazard

Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation Respiratory or skin sensitization

Germ cell mutagenicity

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
COBALT(II) 2-ETHYLHEXANOATE	136-52-7	0.080 - 0.140
STYRENE	100-42-5	20 - 50

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

COBALT(II) 2-ETHYLHEXANOATE (CAS 136-52-7)

STYRENE (CAS 100-42-5)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

STYRENE (CAS 100-42-5) Other Flavoring Substances with OSHA PEL's

US state regulations

California Proposition 65



WARNING: WARNING: This product contains a chemical known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

STYRENE (CAS 100-42-5) Listed: April 22, 2016

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information, including date of preparation or last revision

Issue date 10-11-2024

Version # 01

Disclaimer The information in the sheet was written based on the best knowledge and experience currently

available.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: PENNTROWEL™ VINYL ESTER PRIMER RESIN 5260 Version #: 01 Issue date: 10-11-2024

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).