

# PRECAST PRODUCTS

Sealants & Coatings for Precast Concrete





## Separating good precast structures from those that fail comes down to the details.

Joints are inevitable components of precast concrete construction. Sealing them correctly is vital to the integrity of the system. ErgonArmor's Blackhawk joint sealants provide the proper adhesion, strength and durability to ensure a watertight seal from initial installation through the life of precast structures. Our diverse coatings line for precast applications includes our environmentally friendly Novocoat epoxies. These are 100% solids and offer a VOC-free, user-friendly application for further protection of precast concrete substrates. Novocoat products protect against harsh bacterial and chemical attack and offer outstanding abrasion resistance. The next time you run across a coating specification for your precast job, ask ErgonArmor.



## **Precast Products**

### SEALANTS & COATINGS FOR PRECAST CONCRETE



Precast Sealants	Page
BUTYL SEALANTS  1. BLACKHAWK™ Hawk-Seal  2. BLACKHAWK™ Hawk-Wrap	
MASTIC 3. BLACKHAWK™ 5401 Pipe Joint Mastic	
Precast Protective Coatings	
LIQUID ASPHALT COATINGS  4. BLACKHAWK™ Liquid Asphalt Coating  5. ERTECH™ 2100	
EPOXIES  6. NOVOCOAT™ SC1100 Primer/Sealer  7. NOVOCOAT™ SP2000W Lining  8. NOVOCOAT™ SG2500 Lining	
Precast Release Agents	
FORM RELEASE 9. BLACKHAWK™ Precast Release 50	
Precast Product Specifications	

1

## **Precast Sealants**

### **BUTYL SEALANTS**

### **BLACKHAWK Hawk-Seal – Butyl Joint Sealant**

Blackhawk Hawk-Seal is a high-tack butyl rubber compound used to seal the joints of underground concrete structures such as box culverts, manholes, concrete pipe, septic tanks, utility boxes and vaults. It comes in roll form and functions as a seal against infiltration and exfiltration. The high grade butyl content allows for year round consistent flexibility.





#### **FEATURES:**

- » Asphalt-free
- » No special tools needed
- » Flexible in temperature extremes
- » Excellent chemical resistance
- » ASTM C990-09 compliant



## **BLACKHAWK Hawk-Wrap – External Butyl Joint Wrap**

Blackhawk Hawk-Wrap is a high-tack butyl rubber compound laminated with a tough HDPE backing for added puncture and tear resistance. It comes in roll form and is unrolled over concrete joints. It also functions as a seal against infiltration and exfiltration.





#### **FEATURES:**

- » Asphalt-free
- » No special tools needed
- » Flexible in temperature extremes
- » Excellent chemical resistance
- » ASTM C877-08, Type II, Type A compliant



### MASTIC

### **BLACKHAWK 5401 Pipe Joint Mastic**

Blackhawk 5401 Pipe Joint Mastic is a tough, permanent bituminous sealant of heavy trowel consistency that is impervious to water, sewage and roots. This material seals precast concrete storm and sanitary joints and will not crack or deteriorate under normal service conditions.

#### **FEATURES:**

- » Flexible in temperature extremes
- » Impervious to water, sewage and roots
- » ASTM D4586, Type 1 compliant





## **Precast Protective Coatings**

### LIQUID ASPHALT COATINGS

## **BLACKHAWK Liquid Asphalt Coating**

Blackhawk Liquid Asphalt Coating is a liquefied asphalt coating formulated to be easily applied by roller, brush or spray equipment. It can be used as a coating or as a primer on surfaces receiving Blackhawk Pipe Joint Mastic, Hawk-Seal or Hawk-Wrap. It dries to a tough, durable and water-deterring layer that maintains excellent performance over a wide range of temperatures and conditions. Available in Summer and Winter grades.

#### **FEATURES:**

- » Roll, brush or spray application
- » Solvent-based
- » Wide application temperature range
- » ASTM D4449, Type 1 compliant





## **ERTECH 2100 – Asphalt Emulsion Dampproofing**

Ertech 2100 is a non-fibered asphaltic clay-type emulsion that provides reliable water-based dampproofing on concrete products and can be brushed, rolled or spray applied. It is environmentally friendly and contains fewer VOCs than solvent-based dampproofings.

#### **FEATURES:**

- » Non-hazardous
- » Water-based
- » Environmentally friendly
- » ASTM D1187, Type 1 compliant
- » ASTM D1227, Type III, Class 1 compliant





## **Precast Protective Coatings**

### **EPOXIES**

### **NOVOCOAT SC1100 Primer/Sealer**

Novocoat SC1100 Primer/Sealer is a 100% solids, low viscosity epoxy primer designed for deep penetration and sealing of concrete surfaces. Its slow cure rate makes it ideal for warm weather applications. Novocoat SC1100 Primer/Sealer helps eliminate outgassing and bubbles when the top coat is applied. It can be applied to green concrete as young as seven days.

#### **FEATURES:**

- » 100% solids, no VOCs
- » Can be applied to green concrete as early as seven days
- » Penetrating sealer







## **NOVOCOAT SP2000W Lining**

Novocoat SP2000W Lining is a 100% solids epoxy that contains no VOCs or solvents. It may be safely applied in confined areas with good ventilation. Novocoat SP2000W Lining offers protection for precast concrete structures by guarding against hydrogen sulfide attack and preventing microbially-induced corrosion (MIC).

#### **FEATURES:**

- » 100% solids, no VOCs
- » Excellent immersion resistance
- » Long-term wear protection
- » Meets AWWA C210 requirements







6

## **Precast Protective Coatings**

### **EPOXIES**

## **NOVOCOAT SG2500 Lining – High Build Epoxy Coating**

Novocoat SG2500 Lining is a 100% solids high build epoxy coating suitable for a variety of substrates and applications. Typical applications include wastewater (tanks, lift stations, wet wells and manholes), cooling towers and more. Novocoat SG2500 Lining can also be used as an interior or exterior pipe lining or coating.

### **FEATURES:**

- » 100% solids, no VOCs
- » Can be spray applied at 125 mils in a single pass
- » Excellent immersion resistance





## **Precast Release Agents**

### FORM RELEASE

### **BLACKHAWK Precast Release 50**

Blackhawk Precast Release 50 is a chemically active release agent specially engineered to prevent concrete from bonding to forms in precast and shop use applications.

### **FEATURES:**

- » Fast drying
- » Contains no diesel, waxes or silicones
- » Sprays easily in cold temperatures



## **Precast Product Specifications**

PRODUCT NAME	DIMENSIONS	PRODUCT NUMBER	ROLLS PER CARTON	CARTONS PER PALLET	ROLL LENGTH	SPECIFICATION COMPLIANCE	PRODUCT TYPE	COLOR
BLACKHAWK™ Hawk-Seal	1/2-inch	K-5820-HKS-001	12	27	26 ft	ASTM C990-09  AASHTO M-198  AASHTO SS-S-S210	Butyl Rubber Joint Sealant	Black
	3/4-inch	K-5821-HKS-001	10	36	14.5 ft			
	1-inch	K-5823-HKS-001	8	36	14.5 ft			
	1 1/4-inch	K-5824-HKS-001	6	36	14.5 ft			
	1 1/2-inch	K-5826-HKS-001	6	36	10 ft			
	2-inches	K-5827-HKS-001	4	27	7 ft			
BLACKHAWK™ Hawk-Wrap	6-inches	K-5830-HKW-001	4	20	33 ft	ASTM C877-08 Type III, Type A	External Butyl Rubber Joint Sealant	Black
	9-inches	K-5831-HKW-001	4	20	33 ft			
	12-inches	K-5832-HKW-001	2	20	33 ft			
PRODUCT NAME	CONTAINER	PRODUCT NUMBER	NET CONTENT	PALLET QUANTITY	APPLICATION RATE*	SPECIFICATION COMPLIANCE	PRODUCT TYPE	COLOR
BLACKHAWK™ 5401 Pipe Joint Mastic	5 gallon pail	K-5401-005-001	4.7 gallons	42	18 lbs/36-in joint	ASTM D4586, Type I	Solvent-based Asphalt Cement	Black
BLACKHAWK™ Liquid Asphalt Coating (SG & WG)	5 gallon pail	K-5011-005-001 K-5012-005-001	4.7 gallons	42	ASTM D449, Type I	Solvent-based Asphalt Dampproofing	Black	
	55 gallon drum	K-5011-053-001-UL K-5012-053-001-UL	53 gallons	4	80 ft <sup>2</sup> per gallon at 12 dry mils	дэтм о <del>ччэ</del> , турет	Solvent-based Aspiral Dampprooning	DIACK
ERTECH™ 2100	5 gallon pail	M-2000-005-004	5 gallons	36	ASTM D1187, Type I			
	55 gallon drum	M-2000-053-005	53 gallons	4	80 ft² per gallon at 12 dry mils	ASTM D1227, Type II, Class I ASTM D1227, Type III, Class I	Water-based Asphalt Dampproofing	Black
NOVOCOAT™ SC1100 Primer/Sealer	Small Kit	M-SC1100-SMKT-01	1 mixed gallon	- Varies	320 ft <sup>2</sup> per gallon at 5 dry mils			
	Large Kit	M-SC1100-LGKT-01	4.8 mixed gallons				100% Solids Epoxy Primer	Amber/Clear
NOVOCOAT™ SP2000W Lining	1 gallon kit	M-SP2310-1GLKT-01	1 mixed gallon	Varies	160 ft² per gallon at 10 dry mils	s ASTM D4541 (Adhesion Test)	100% Solids Epoxy Coating	Gray (Other Colors Available)
	4 gallon kit	M-SP2310-4GLKT-01	4 mixed gallons					
NOVOCOAT™ SG2500 Lining	5 gallon pail	M-SG2510A-5GLB-01 M-SG2508B-5GLB-01	5 gallons	Varies	Varies 50 ft² per gallon at 30 dry mils 12 ft² per gallon at 125 dry mils	ASTM D4541 (Adhesion Test) Meets AWWA C210 performance requirements	100% Solids Polyamide Epoxy Coating	Green (Other Colors Available)
	55 gallon drum	M-SG2510A-DRUM-01 M-SG2508B-DRUM-01	50 gallons					
BLACKHAWK <sup>™</sup> Precast Release 50	5 gallon pail	K-6003-005-001	5 gallons	36	1000 – 2000 ft² per gallon			
	55 gallon drum	K-6003-053-001	53 gallons	4			Oil-based Reactive Release Agent	Colorless Liquid
	275 gallon tote	K-6003-275-001	275 gallons	1				

<sup>\*</sup>Application rates are approximate and can vary based on substrate and application.

10 11



### **About ErgonArmor:**

You've built it. Now let ErgonArmor protect it.

We provide advanced surface protection solutions to a diverse range of harsh environments. With ErgonArmor, you can be assured that our depths and strengths stand behind the solutions we offer. Let us be the manufacturing and technical resource you turn to for answers in protecting and maintaining the investment you have made in your industry.



ergonarmor.com 877-982-7667 + 1 601-933-3595 ErgonArmorCustServ@Ergon.com

### **Ordering Information**

For additional information, prices or to place an order, please contact your ErgonArmor sales representative. If you do not know the name of your sales representative, call **877-98ARMOR**.

